

SECTION1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product code: SABART - FORESTAL POWER ON STARTER SPRAY

Trades code: R331220

UFI: 50WT-YDK0-JR3A-VARU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Starter

Sectors of use:

Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Product category:

Automotive Care Products

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Everton srl - Via Azzano 11 37064 Povegliano Veronese (VR) Tel. + 39 045/6350595 Fax +39 045/6350653

Email: info@everton.it - Sito internet: www.everton.it

Email tecnico competente: erik.ballanti@everton.it

1.4. Emergency telephone number

Emergency telephon number EU 112

SECTION2. Hazards identification**2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS02, GHS07, GHS08

Hazard Class and Category Code(s):

Flam. Aerosol 1, Acute Tox. 4, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3

Hazard statement Code(s):

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H302 - Harmful if swallowed.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Aerosol that ignites easily even at low temperatures, fire risk

Harmful product: do not ingest

If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

Warning: Vapours inhalation may cause sleepiness and giddiness

Issued on 09/03/2024 - Rel. # 1 on 09/03/2024

2 / 14

In conformity to Regulation (EU) 2020/878

The product is dangerous to the environment as it is harmful to aquatic life with long lasting effects
The repeated inhalation of vapors can cause drowsiness and giddiness.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

The classification has been calculated net of the propellants.
According to 1.3.3 of Annex I to Reg. (EC) 1272/2008, the statements related to aspiration hazard are excluded from the labelling elements.

2.1.2 Additional information:

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS02, GHS07 - Danger



Hazard statement Code(s):
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Supplemental Hazard statement Code(s):
EUH019 - May form explosive peroxides.
EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing spray.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

P312 - Call a POISON CENTER or a doctor if you feel unwell.

Storage

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Contains:

Hydrocarbons, C6, isoalkanes, < 5% n-hexane

Packaging to be fitted with a tactile warning
Content of VOC ready to use condition: 80,41 %

UFI: 50WT-YDK0-JR3A-VARU

2.3. Other hazards

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

No information on other hazards

SECTION3. Composition/information on ingredients

3.1 Substances

Irrrelevant

3.2 Mixtures

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
propane Note: U	>= 30 < 50%	Flam. Gas 1A, H220; Press. Gas, H280 ATE inhal = 658,000 mg/l/4 h	601-003-00-5	74-98-6	200-827-9	01-2119486 944-21
diethyl ether	>= 24 < 30%	EUH019; EUH066; Flam. Liq. 1, H224; Acute Tox. 4, H302; STOT SE 3, H336 ATE oral = 200,000 mg/kg ATE inhal = 20,000 mg/l/4 h	603-022-00-4	60-29-7	200-467-2	01-2119535 785-29
butane Note: C U	>= 19 < 24%	Flam. Gas 1A, H220; Press. Gas, H280 ATE inhal = 658,000 mg/l/4 h	601-004-00-0	106-97-8	203-448-7	01-2119474 691-32
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	>= 15 < 19%	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 2, H411 ATE oral > 16.750,000 mg/kg ATE dermal > 3.350,000 mg/kg ATE inhal > 260,000	ND	ND	931-254-9	01-2119484 651-34

Issued on 09/03/2024 - Rel. # 1 on 09/03/2024

4 / 14

In conformity to Regulation (EU) 2020/878

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
		mg/l/4 h				

SECTION4. First aid measures**4.1. Description of first aid measures**

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated room.
CALL A PHYSICIAN.

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area.
If you feel unwell seek medical advice.

If breathing has stopped, give artificial respiration.

Direct contact with skin (of the pure product).:

Take contaminated clothing Immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

Direct contact with eyes (of the pure product).:

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

The product is harmful and can cause irreversible damages even following a single exposure if swallowed.

Absolutely do not induce vomiting or emesis. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to substances refer to paragraph 11.

4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation occurs: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

Call a POISON CENTER or a doctor if you feel unwell.

SECTION5. Firefighting measures**5.1. Extinguishing media**

Advised extinguishing agents:

CO2 or dry powder extinguisher

Extinguishing means to avoid:

Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****6.1.1 For non-emergency personnel:**

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear mask, suitable gloves (PVC, butyl rubber, neoprene or similar) and protective clothing.

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up**6.3.1 For containment:**

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION7. Handling and storage**7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors

Wear protective gloves/protective clothing/eye protection/face protection.

Use extreme caution when handling the product. Avoid shock or friction.

In residential areas do not use on large surfaces.

Do not smoke at work

At work do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

Do not eat, drink or smoke when using this product.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

7.3. Specific end use(s)

Private households (= general public = consumers):

- ☐ Keep away from heat sources, sparks, open flames
- ☐ Do not use on hot surfaces or surfaces exposed to direct sunlight
- ☐ Do not breathe spray/vapours
- ☐ Avoid contact with eyes, skin, clothing
- ☐ Do not eat, drink or smoke when using
- ☐ Do not use in confined and/or limited spaces
- ☐ Accumulations of flammable gas in the air may occur in case of an excessive use
- ☐ Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- ☐ Spray only briefly and take care for a good ventilation after use

Public domain (administration, education, entertainment, services, craftsmen):

- ☐ Keep away from heat sources, sparks, open flames
- ☐ Do not use on hot surfaces or surfaces exposed to direct sunlight
- ☐ Do not breathe spray/vapours
- ☐ Avoid contact with eyes, skin, clothing
- ☐ Do not eat, drink or smoke when using
- ☐ Do not use in confined and/or limited spaces
- ☐ Accumulations of flammable gas in the air may occur in case of an excessive use
- ☐ Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- ☐ Spray only briefly and take care for a good ventilation after use

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:

diethyl ether:

TLV-TWA: 400 ppm (ACGIH 2024)

TLV-STEL: 500 ppm (ACGIH 2024)

OEL 8h: 100 ppm - 308 mg/m³ (Directive 2000/39/EC – Occupational exposure limit values)

OEL short term: 200 ppm - 616 mg/m³ (Directive 2000/39/EC – Occupational exposure limit values)

MAK: 400 ppm - 1200 mg/m³

Peak limitation category: I(1)

Pregnancy risk group: D (DFG 2008)

butane:

TLV-TWA: 1000 ppm (ACGIH 2024)

Hydrocarbons, C6, isoalkanes, < 5% n-hexane:

TLV-TWA: 100 ppm (as hexane, other isomers, ACGIH 2024)

- Substance: diethyl ether

DNEL

Systemic effects Long term Workers inhalation = 308 (mg/m³)

Systemic effects Long term Workers dermal = 44 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 54,5 (mg/m³)

Systemic effects Long term Consumers dermal = 15,6 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 15,6 (mg/kg bw/day)

Systemic effects Short term Workers inhalation = 616 (mg/m³)

PNEC

Sweet water = 2 (mg/l)

sediment Sweet water = 9,14 (mg/kg/sediment)

Sea water = 0,2 (mg/l)

STP = 4,2 (mg/l)

ground = 0,66 (mg/kg ground)

- Substance: Hydrocarbons, C6, isoalkanes, < 5% n-hexane

DNEL

Systemic effects Long term Workers inhalation = 5306 (mg/m³)

Systemic effects Long term Workers dermal = 13964 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 1131 (mg/m³)

Systemic effects Long term Consumers dermal = 1377 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 1301 (mg/kg bw/day)

8.2. Exposure controls

Appropriate engineering controls:

Private households (= general public = consumers):

Work in a well ventilated place or equipped with ventilation devices. Do not use on hot surfaces or surfaces exposed to sunlight in order to avoid rapid evaporation of the product. Use personal protective equipment (see below).

Public domain (administration, education, entertainment, services, craftsmen):

Ensure good ventilation in the workplace through effective local aspiration. If these steps are not enough to maintain the concentration of the product below the exposure limit values in the workplace, wear appropriate respiratory protection.

Provide a system for eye wash. Before using the product refer to the label for hazard details. During the selection of personal protective equipment, seek appropriate advice from the supplier. Personal protective equipment must comply with regulations in force.

Individual protection measures:

(a) Eye / face protection

Wear safety goggles (compliant to EN 166 or EN ISO 16321)

(b) Skin protection

(i) Hand protection

Wear protective gloves against dangerous chemicals (compliant to EN ISO 374-1/-2/-3).

Gloves material: nitrile

Thickness: 0,40 mm

Breakthrough time: > 480 min

(ii) Other

When handling the product wear full protective skin clothing and safety footwear (compliant to EN ISO 20345).

Better is to use cotton antistatic clothing

(c) Respiratory protection

Work in a sufficiently ventilated to avoid inhaling the product.

Where the OEL may be approached or exceeded, wear mask with AX or universal filter (compliant to EN ISO 14387).

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Physical state	liquid under pressure	VISUAL
Colour	colorless	
Odour	characteristic, of ether	ORGANOLEPTIC
Odour threshold	not determined	
Melting point/freezing point	< 0 °C (liquid)	
Boiling point or initial boiling point and boiling range	> -42 °C (liquid gas)	
Flammability	extremely flammable aerosol	
Lower and upper explosion limit	LEL 1,8 % (vol); UEL 9,5 % (vol)	
Flash point	irrelevant	
Auto-ignition temperature	> 400 °C (liquid gas)	
Decomposition temperature	irrelevant	
pH	the mixture is non-polar/aprotic	PH-METER
Kinematic viscosity	not determined	
Solubility	in common organic solvents	
Water solubility	7.5% at 20 °C (ether)	
Partition coefficient n-octanol/water (log value)	irrelevant	
Vapour pressure	3,2 bar	
Density and/or relative density	0,68 kg/l	
Relative vapour density	> 2 (liquid gas)	
Particle characteristics	irrelevant	

9.2. Other information

Content of VOC ready to use condition: 80,41 %

9.2.1 Information with regard to physical hazard classes

Irrilevant

9.2.2 Other safety characteristics

Irrilevant

SECTION 10. Stability and reactivity**10.1. Reactivity**

Related to contained substances:
diethyl ether:

The substance can form explosive peroxides under the influence of light and air. Reacts violently with halogens, interhalogens, sulfur compounds and oxidants causing fire and explosion hazard. Attacks plastic and rubber.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire.

Avoid heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 °C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, strong reducing agents.

It can generate toxic gases to contact with oxidants mineral acids, organic peroxides, organic water peroxides.

It can ignite in contact with oxidants mineral acids, organic nitrides, peroxides and water peroxides, strong oxidants agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

ATE(mix) oral = 769,2 mg/kg

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

(a) acute toxicity: Harmful product: do not ingest

(b) skin corrosion/irritation: If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

(c) serious eye damage/irritation: based on available data, the classification criteria are not met.

(d) respiratory or skin sensitisation: based on available data, the classification criteria are not met.

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: based on available data, the classification criteria are not met.

SABART - FORESTAL POWER ON STARTER SPRAY

Issued on 09/03/2024 - Rel. # 1 on 09/03/2024

10 / 14

In conformity to Regulation (EU) 2020/878

- (h) specific target organ toxicity (STOT) single exposure: Warning: Vapours inhalation may cause sleepiness and giddiness
- (i) specific target organ toxicity (STOT) repeated exposure: based on available data, the classification criteria are not met.
- (j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

propane:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation.

INHALATION RISK: On loss of containment this liquid evaporates very quickly displacing the air and causing a serious risk of suffocation when in confined areas.

EFFECTS OF SHORT-TERM EXPOSURE: Rapid evaporation of the liquid may cause frostbite. The substance may cause effects on the central nervous system.

ACUTE HAZARDS/SYMPTOMS

INHALATION Drowsiness. Unconsciousness.

SKIN ON CONTACT WITH LIQUID: FROSTBITE.

EYES ON CONTACT WITH LIQUID: FROSTBITE.

N O T E S High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death.

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658

diethyl ether:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

INHALATION RISK: A harmful contamination of the air can be reached rather quickly on evaporation of this substance at 20°C.

EFFECTS OF SHORT-TERM EXPOSURE: The substance is irritating to the eyes and the respiratory tract. If this liquid is swallowed, aspiration into the lungs may result in chemical pneumonitis. The substance may cause effects on the central nervous system, resulting in narcosis.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin. The substance may have effects on the central nervous system. Caution, may cause addiction.

ACUTE HAZARDS/SYMPTOMS

INHALATION Cough. Sore throat. Drowsiness. Vomiting. Headache. Laboured breathing. Unconsciousness.

SKIN Dry skin.

EYES Redness. Pain.

INGESTION Dizziness. Drowsiness. Vomiting.

N O T E S Use of alcoholic beverages enhances the harmful effect.

LD50 (rat) Oral (mg/kg body weight) = 200

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20

butane:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation.

INHALATION RISK: On loss of containment this liquid evaporates very quickly displacing the air and causing a serious risk of suffocation when in confined areas.

EFFECTS OF SHORT-TERM EXPOSURE: Rapid evaporation of the liquid may cause frostbite. The substance may cause effects on the central nervous system.

ACUTE HAZARDS/SYMPTOMS

INHALATION Drowsiness. Unconsciousness.

SKIN ON CONTACT WITH LIQUID: FROSTBITE.

EYES ON CONTACT WITH LIQUID: FROSTBITE.

N O T E S High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death.

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658

Hydrocarbons, C6, isoalkanes, < 5% n-hexane:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation of its vapour and through the skin.

INHALATION RISK: A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20 °C.

EFFECTS OF SHORT-TERM EXPOSURE: The substance is irritating to the eyes and the skin. The vapour irritates the eyes, the skin and the respiratory tract. If this liquid is swallowed, aspiration into the lungs may result in chemical pneumonitis. The substance may cause effects on the central nervous system.

Issued on 09/03/2024 - Rel. # 1 on 09/03/2024

11 / 14

In conformity to Regulation (EU) 2020/878

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin. The substance may have effects on the liver, resulting in impaired functions.

ACUTE HAZARDS/SYMPTOMS

INHALATION Dullness. Headache.

SKIN Dry skin.

EYES Redness. Pain.

INGESTION Abdominal cramps. Burning sensation. Nausea. Vomiting.

LD50 (rat) Oral (mg/kg body weight) > 16750

LD50 Dermal (rat or rabbit) (mg/kg body weight) > 3350

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) > 260

11.2. Information on other hazards

No data available.

11.2.1. Endocrine disrupting properties

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

propane:

Toxicity to fish

- LC50, 96h = 53,41 mg/l (literature value)

Toxicity to daphnia and other aquatic invertebrates

- EC50 Daphnia magna, 48h = 29,66 mg/l

Toxicity to algae

- EC50, 96h = 20,58 mg/l (literature value)

butane:

Toxicity to fish

- LC50, 96h = 24,11 mg/l (literature value)

Toxicity to daphnia and other aquatic invertebrates

- EC50 Daphnia magna, 48h = 14,22 mg/l

Toxicity to algae

- EC50, 96h = 7,71 mg/l (literature value)

Hydrocarbons, C6, isoalkanes, < 5% n-hexane:

Toxicity to daphnia and other aquatic invertebrates

- EC50 Daphnia magna, 48h = 3,87 mg/l

Toxicity to algae

- IC50 Scenedesmus subspicatus, 72h = 55 mg/l

The product is dangerous for the environment as it is toxic for aquatic organisms following acute exposure.

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

Related to contained substances:

propane:

Readily biodegradable

butane:

Readily biodegradable

12.3. Bioaccumulative potential

Related to contained substances:

propane:

Log Pow $\leq$ 2,35

butane:

Log Pow $\leq$ 2,8**12.4. Mobility in soil**

No data available.

12.5. Results of PBT and vPvB assessment

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

12.6. Endocrine disrupting properties

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

12.7. Other adverse effects

No adverse effects

SECTION13. Disposal considerations**13.1. Waste treatment methods**

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 °C can burst.

Recover if possible. Operate according to local or national regulations

SECTION14. Transport information**14.1. UN number or ID number**

ADR/RID/IMDG/ICAO-IATA: 1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 kg

Inner packagings placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 kg

**14.2. UN proper shipping name**

ADR/RID/IMDG: AEROSOL infiammabili

ADR/RID/IMDG: AEROSOL flammable

ICAO-IATA: AEROSOL flammable

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class: 2

ADR/RID/IMDG/ICAO-IATA: Label: 2.1

ADR: Tunnel restriction code: D

Issued on 09/03/2024 - Rel. # 1 on 09/03/2024

13 / 14

In conformity to Regulation (EU) 2020/878

ADR/RID/IMDG/ICAO-IATA: Limited quantities: 1 L
IMDG - EmS: F-D, S-U

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: --

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous
IMDG: Marine polluting agent: Not

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions.
The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Maritime transport in bulk according to IMO instruments

It is not intended to carry bulk

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2012/18/EU, annex I, part 1

Control of Substances Hazardous to Health (COSHH), Regulations 2002

Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII to Regulation EC 1907/2006):

Designation of the substance, of the group of substances or of the mixture: 40 - Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Regulation 2006/1907/EC (REACH), Regulation 2008/1272/EC (CLP).

Seveso category:

P3a - FLAMMABLE AEROSOLS

REGULATION (EU) No 1357/2014 - waste:

HP3 - Flammable

HP4 - Irritant — skin irritation and eye damage

HP5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Substances in the Candidate List (REACH Article 59)

Based on available data, no SVHC substances are present

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information**16.1. Other information**

Description of the hazard statements exposed to point 3

- H220 = Extremely flammable gas.
- H280 = Contains gas under pressure; may explode if heated.
- H224 = Extremely flammable liquid and vapour.
- H302 = Harmful if swallowed.
- H336 = May cause drowsiness or dizziness.
- H225 = Highly flammable liquid and vapour.
- H304 = May be fatal if swallowed and enters airways.
- H315 = Causes skin irritation.
- H411 = Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008

- H222 - Extremely flammable aerosol. Classification procedure: On basis of test data
- H229 - Pressurised container: May burst if heated. Classification procedure: On basis of test data
- H302 - Harmful if swallowed. Classification procedure: Calculation method
- H315 - Causes skin irritation. Classification procedure: Calculation method
- H336 - May cause drowsiness or dizziness. Classification procedure: Calculation method
- H412 - Harmful to aquatic life with long lasting effects. Classification procedure: Calculation method

Main normative references:

Regulation 1907/2006/EC

Regulation 1272/2008/EC

Regulation (EU) 2020/878

*** This tab annuls and replaces any previous edition.
